

POLYFLOR PRESTIGE PUR

- BRE Global Environmental A+ Rating ENP 336
- Attractive, high-performance, heavy duty floorcovering
- Polyurethane reinforcement for a low cost, lifetime polish-free maintenance regime

SPECIFICATION



2.0mm



2m x 20m = 40m²



300 x 300mm = 4.5m²
608 x 608mm = 5.17m²



3030g/m²



GENERAL PERFORMANCE

EN 649
ASTM F1913
ASTM F1700



REACTION TO FIRE

EN 13501-1 Class Bfl-S1
ASTM E662 <450
EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass
ASTM E648 Class 1



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 649 Group P



ELECTRICAL BEHAVIOUR
(body voltage)
EN 1815 ≤2kV
Classified as 'antistatic'



CASTOR CHAIR
(continuous use)
Suitable



INDENTATION RESIDUAL
ASTM F970 (Modified)
Static load 750psi



VOC EMISSIONS
AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
Finnish M1 Classification: Pass
Ecospecifier Green Tag: Pass



ENVIRONMENTALLY PREFERABLE FLOORING

BRE Global Environmental A+ Rating ENP 336 in the Green Guide to Specifications. Polyflor Prestige PUR is 100% recyclable and contains 25% recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



AGRÉMENT ASSURANCE

Polyflor Prestige PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



APPLICATIONS

Polyflor Prestige PUR is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Hulet
FLOORING



March 2011



POLYFLOR
PRESTIGE PUR
HOMOGENEOUS



PERFORMANCE AND
PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com

