


# Polysafe™ Stone fx PUR

Polysafe Stone fx PUR is a heavy-duty safety flooring collection in a range of high clarity stone and concrete effects. Clear aluminium oxide particles which are virtually invisible to the naked eye are integrated throughout the performance layer to provide a safety flooring which is both functional and beautiful. These caborundum-free safety particles ensure that Polysafe Stone fx PUR offers full HSE compliance and sustainable wet slip resistance. For use in heavy commercial and residential installations including education, health and care, social housing, leisure and retail sectors.



## PRODUCT SPECIFICATION

- The flooring shall be Polysafe Stone FX PUR, as manufactured by Polyflor Ltd. of Manchester, England.
  - The flooring shall be flexible PVC sheet flooring in 2.0mm thickness, with the following construction: circa 0.7mm clear PVC wear layer with aluminium oxide granules incorporated throughout the full thickness - to impart enhanced slip resistance, a fibreglass reinforced integral print layer and circa 1.30mm of PVC backing.
  - The flooring shall feature a high quality, cross-linked polyurethane reinforcement to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.
- 
- The flooring material shall fully conform with the European Norm for safety flooring - EN 13845.
  - In respect of flamespread, the flooring shall be categorised as Class Bfl-S1 according to EN 13501-1. The flooring shall have been fully tested to ASTM E648 by an independent test house and have a Class 1 rating, making it suitable for use in institutional, commercial and public buildings.
  - The flooring must have been fully tested by an independent test house to the RRL Pendulum Test (4S Rubber/Slider 96) and have results of  $\geq 36$  in the wet, with a surface roughness of  $Rz \geq 20\mu m$ , making it suitable for use in areas where enhanced slip resistance is required.
  - The product must have been fully tested for abrasion resistance to EN 13845, passing the 50,000 cycles test and also meeting EN 649 Abrasion Group T.
  - The flooring shall possess a valid Agrément certificate when laid in accordance with the instructions of Polyflor, with coved skirtings and welded joints.
  - This product does not accumulate static charges above 2kV and is classified as 'antistatic' when tested to EN 1815. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.
  - The flooring must be available in 2.01 metre width, including a 0.01 metre selvege for on-site trimming, to minimise the number of joints.
  - The flooring is suitable for Use Area Classification 23/34/43, as defined in EN ISO 10874 (EN 685).
  - In respect of light fastness, the flooring shall have been fully tested to ISO 105-B02 Method 3 and obtain  $\geq 6$
- 
- Polysafe Stone fx PUR achieves a BRE Global Environmental Generic A rating in the Green Guide to Specification.
  - Generic EN 15804 Environmental Product Declaration (EPD) available on request.
  - The manufacturer should provide a facility to take back and recycle waste vinyl flooring material through the Recofloor scheme.
  - The flooring shall be tested to and pass key independent, international standards for low VOC emissions.
- 
- The manufacturer of the floorcovering must be in possession of a valid quality systems certificate, showing compliance with ISO 9001.
  - The manufacturer of the floorcovering must be in possession of a valid environmental certificate, showing compliance with ISO 14001.
- 
- A moisture test must be carried out to ensure that the subfloor has dried out to a level consistent with the application of vinyl flooring. The test should be carried out using a hygrometer, in accordance with the instructions in BS 8203. The result should not exceed 75%RH, once equilibrium has been achieved.
  - The adhesive used must be approved by Polyflor, to ensure full product compatibility.
  - Products must be fully conditioned to the environment in which they are to be installed, as outlined by Polyflor.
  - Installation must be carried out in accordance with BS 8203 and the instructions of Polyflor.
  - All joints must be welded to produce hygienic, continuous floors.
  - Suitable for use with underfloor heating up to 27°C. See Polyflor Technical Information Manual for details.
- 
- Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com). The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.
- As with all Polysafe products, Polysafe Stone fx PUR should not have a polish applied.  
The data presented is correct at the time of printing. For latest information, please visit our website [polyflor.com](http://polyflor.com).



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913  
Sample Requests: +44 (0)161 767 2551 | email: [info@polyflor.com](mailto:info@polyflor.com) | [www.polyflor.com](http://www.polyflor.com)



September 2019